



Модель	A(H7)	B	C	D	E(h7)	F	G	H(H8)	I(h7)	J	K(H7)	L	N	O	P	Q	R(max)	R(min)	S
TF-CC1336-S	50	M55XP2.0	65	75	100	165	40	36	50	M52XP1.5	76	85	130	15	25	10	13	-3	4
TF-CC1346-S	50	M55XP2.0	65	75	100	165	40	46	50	M52XP1.5	76	85	130	15	30	10	13	-3	4
TF-CC1446-S	55	M60XP2.0	70	80	130	188	40	46	56	M58XP1.5	85	96	140	15	30	12	19	-3	5
TF-CC1452-S	55	M60XP2.0	70	80	130	188	40	52	56	M58XP1.5	85	96	140	15	30	12	19	-3	5
TF-CC1768-S	80	M85XP2.0	95	105	160	214	46	68	81	M84XP2.0	108	121	140	15	35	11	22	-3	5
TF-CC1775-S	80	M85XP2.0	95	105	160	214	46	75	81	M84XP2.0	108	121	170	15	35	11	22	-3	5
TF-CC1777-S	82	M87XP2.0	95	105	160	214	46	78	81	M84XP2.0	108	121	170	15	35	11	22	-3	5

Модель	T	V	W(max)	W(min)	X(max)	X(min)	Y	Z	a	b	c1	d	e	f	g1	h	i	k1	-
TF-CC1336-S	131	4	45	29	30	14	102.6	10.5	64	103.5	76	RC3/8	M5	M6	M5	147	165	90.5	-
TF-CC1346-S	131	4	45	29	30	14	102.6	10.5	64	103.5	76	RC3/8	M5	M6	M5	147	165	90.5	-
TF-CC1446-S	137.45	4	48.55	26.55	36	14	109.7	8.5	73	120	83.5	RC3/8	M6	M6	M5	165	188	97.7	-
TF-CC1452-S	137.45	4	48.55	26.55	36	14	109.7	8.5	73	120	83.5	RC3/8	M6	M6	M5	165	188	97.7	-
TF-CC1768-S	157	4	53	28	39	14	119.6	13.25	98	150	100	RC1/2	M6	M6	M5	195	216	102.63	-
TF-CC1775-S	157	4	53	28	39	14	119.6	13.25	98	150	100	RC1/2	M6	M6	M5	195	216	102.63	-
TF-CC1777-S	157	4	53	28	39	14	119.6	13.25	98	150	100	RC1/2	M6	M6	M5	195	216	102.63	-